DATA SHEET



LED INDUSTRIAL LAMP WITH DIMMABLE DRIVER 150W, 5000K, 220V, SMD3030, IP65

LIK15050



DESCRIPTION

LED lighting fixture LIK15050 is suitable for lighting of industrial, warehouse and production buildings, replacing the old low-efficient fixtures. It is known by its high energy efficiency 145 lm/W, innovative and light shock-resistant body IK08, easy and fast mounting. The high index of protection IP65 makes this fixture suitable for indoor and outdoor installation. It drastically decreases electricity expenses.

The body has a breathing device/valve that prevents the penetration of moisture into the body. An advantage of the LED body is that it can be dimmed by 1-10 VDC and PWM 10V. It has a bracket and a ring, which allow you to choose the way of installation.

BENEFITS

- High efficiency 145 lm/W
- Quickly and easily change of the light distribution (60°, 90°)
- Built-in dimming driver, 1-10 VDC and PWM 10V
- Flickerless
- Breathing device/valve
- IP65
- Optimal size and weight.
- Bracket and ring, which allow you to choose the way of installation
- Warranty period: 5 years

APPLICATION

- Indoor and outdoor installation
- Warehouses
- Industrial lighting
- Sport facilities



• Efficiency: 145 lm/W

• Rated luminous flux: 21500 lm

• Flicker: <5%

• Color Rendering Index (CRI): >80

• Beam angle: 60/90 °

• Correlated Color Temperature (CCT): 5000 K

• LED type: SEOUL SMD3030

Electrotechnical information

Voltage: 200-240 V AC
Frequency: 50-60 Hz
Power factor: >0.95
Power: 150 W
Driver: SOSEN

Basic information

Type of protection: IP65Impact protection rate: IK08

• Working temperature: -20 °C ÷ +45 °C

• On/Off Cycles: >30 000

• Lumen Maintenance L80B50: >50 000 h

• Dimensions: Ø340/190 mm

Weight: 5.10 kgWarranty: 5 years



